

MODEL CPNL - ETHERNET AND USB PANEL-MOUNT CONNECTORS




- DUST- AND WATER-PROOF TO IP68 WITH SEALING CAP ATTACHED
- CAT 5E COMPLIANT ETHERNET CONNECTION
- ETHERNET DATA RATE UP TO 100MHZ
- USB VERSION 2.0 PERFORMANCE
- USB HOT PLUGGABLE, STANDARD 4 POLE INTERFACE

Version 1: A type USB front of panel, standard B type at rear


Version 2: B type USB front of panel, standard A type at rear

DESCRIPTION

Ethernet (RJ-45) and USB panel-mount connectors are available for use in those installations where access to HMI, Data Station Plus or Modular Controller modules is awkward, or where easy access to Ethernet and/or USB connections is simply desirable. These connectors are supplied with an o-ring sealed cap that maintains their IP68 dust- and water-proof rating. The screw cap is easily removed for quick access to the Ethernet and USB connections. All connectors are provided with panel sealing gasket and o-ring sealed screw cap. Standard patch cables are used to connect the device to the rear of the panel-mount connector.



APPLICATION EXAMPLE



ORDERING INFORMATION

MODEL NO.	DESCRIPTION	PART NUMBER
CPNL	RJ-45 to RJ-45 Panel-mount Connector	CPNLRJ45
	USB Type A Front to USB Type B Rear Panel-mount Connector *	CPNLUSBA
	USB Type B Front to USB Type A Rear Panel-mount Connector **	CPNLUSBB

* Use this connector to remote mount the device's USB host ports.

** Use this connector to remote mount the device's programming port.

LIMITED WARRANTY

The Company warrants the products it manufactures against defects in materials and workmanship for a period limited to two years from the date of shipment, provided the products have been stored, handled, installed, and used under proper conditions. The Company's liability under this limited warranty shall extend only to the repair or replacement of a defective product, at The Company's option. The Company disclaims all liability for any affirmation, promise or representation with respect to the products.

The customer agrees to hold Red Lion Controls harmless from, defend, and indemnify RLC against damages, claims, and expenses arising out of subsequent sales of RLC products or products containing components manufactured by RLC and based upon personal injuries, deaths, property damage, lost profits, and other matters which Buyer, its employees, or sub-contractors are or may be to any extent liable, including without limitation penalties imposed by the Consumer Product Safety Act (P.L. 92-573) and liability imposed upon any person pursuant to the Magnuson-Moss Warranty Act (P.L. 93-637), as now in effect or as amended hereafter.

No warranties expressed or implied are created with respect to The Company's products except those expressly contained herein. The Customer acknowledges the disclaimers and limitations contained herein and relies on no other warranties or affirmations.

Red Lion Controls
Headquarters
20 Willow Springs Circle
York PA 17406
Tel +1 (717) 767-6511
Fax +1 (717) 764-0839

Red Lion Controls
Europe
Printerweg 10
NL - 3821 AD Amersfoort
Tel +31 (0) 334 723 225
Fax +31 (0) 334 893 793

Red Lion Controls
India
54, Vishvas Tenement
GST Road, New Ranip,
Ahmedabad-382480 Gujarat, India
Tel +91 987 954 0503
Fax +91 79 275 31 350

Red Lion Controls
China
Unit 101, XinAn Plaza
Building 13, No.99 Tianzhou Road
ShangHai, P.R. China 200223
Tel +86 21 6113-3688
Fax +86 21 6113-3683